



SIMPO 5000i

51.2V 3U Battery System
5.12kWh/100Ah

SIMPO 5000i

System Data	
Battery Type	LiFePO4 (Lithium Iron Phosphate)
Capacity	100Ah
Energy(Usable)	5.12kWh
Nominal Voltage	51.2V
Voltage Range	40.8V~58.08V
Depth Of Discharge	100%
Weight	44kg
Dimension(WxHxD)	440mm×134mm×480mm
Maximum Continuous Current	100A
Peak Current(5 Seconds)	150A
Efficiency(@0.5C)	95.0%
Communication	CAN / RS485 / No-Com
Cycle Life	> 6,000 (@25°C)
Certificates	UN38.3, CE, IEC62619
Charging Temperature	-0°C~+55°C
Discharging Temperature	-10°C~+55°C
Scalability	Max 64 Units In Parallel

10 Benefits To Easy Your Project



Communication Free Mode

2 com options, CAN/RS485 communication managed & communication free self-managed



Integrated Air Switch

Advanced system protection, ensuring the utmost safety for your power supply



Pre-Wired Cabinet

Pre-wired battery cabinets to suit 6 or 10 batteries for ease of installation and better space utilisation



Portal Monitoring

Simplify monitoring and control of your energy storage projects with a personalized online portal



Hot Swappable

Easy maintenance, without interruption of system running



Auto Setup

Automated setup, no app needed. Start running the system in minutes with a quick installation



64 Max Scalability

Up to 64 units in parallel, no extra communication parts needed, with a standard 19-inch rack design for maximum project flexibility



High C Rate

Power class increased with pre-wired DC busbar. Maximize the system power, minimize the battery size



10 Years Warranty

10 Years 60% performance warranty. We stand by the high quality and reliability of our solutions



No Communication Hub

No extra communication hub needed for parallel connections. Each battery can be the master to manage the whole system